

## CLEVERTRONICS LP ODYSSEY QUANTUM 600MM LED DIFFUSED BATTEN (ZONWORKS)



### PRODUCT INFORMATION

Catalogue Number	CBS2LEDS-DIF-ZW
MIC	AUB02110060001
Description	LP Premium Quantum 600mm LED Diffused Batten with LED Emergency Pod
Construction	Powder Coated Steel Body with Acrylic Prismatic Diffuser and PC/ABS End Caps
Mounting	Surface Mount
Dimensions L x W x H	664mm x 120mm x 108mm
Weight	2.0 kg
Operating Mode	Sustained
Testing System	Zoneworks Computerised Testing
Battery	Lithium Iron Phosphate 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Acrylic Prismatic
Driver / Ballast	Osram 40W, 500-1050mA, 15-50V
Lamp(s)	LED Strip Module, 4,000K Natural White, 50,000h Life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	2200lm @ 105lm/W
Power Consumption	20W (Lamps ON) 0.4W (Lamps OFF, Standby)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D40 C <sub>90</sub> =D40

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
8002695	PCA:LED Strip 8S6P, ALS-13-840-0-02-B
1330029	LED XZ Driver – 40w 500mA, 15-50V
CLIFE-CKIT-NP	Lifelight, Control Only, LP, No Plug
8001450	PCA:Powerline Node ZW, #CT10310-A6

*The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order*