

CLEVERTRONICS LP ODYSSEY QUANTUM 1200MM LED DIFFUSED BATTEN (DALI)



PRODUCT INFORMATION

Catalogue Number	CBS4LEDS-DIF-DALI
MIC	AUB02210990002
Description	LP Premium Quantum 1200mm LED Diffused Batten with LED Emergency Pod
Construction	Powder Coated Steel Body with Acrylic Prismatic Diffuser and PC/ABS End Caps
Mounting	Surface Mount
Dimensions L x W x H	1271mm x 120mm x 108mm
Weight	3.3kg
Operating Mode	Sustained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate LP 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Acrylic Prismatic
Driver / Ballast	LED XZ Driver – 50w 700mA, 30-54V
Lamp(s)	LED Strip Module, 4,000K Natural White, 50,000h Life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	4585lm @115lm/W
Power Consumption	39W (Lamps ON), 0.4W (Lamps OFF, Standby)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
8002695	PCA:LED Strip 8S6P, ALS-13-840-0-02-B
1330059	LED XZ Driver – 50w 700mA, 30-54V
CLIFE-CKIT-NP	Lifelight, Control Only, LP, No Plug
8003060	PCA: New DALI #CT10629-Ax

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order