

CLEVERTRONICS LP ODYSSEY QUANTUM LED DIFFUSED BATTEN LOW POWER OUTPUT



PRODUCT INFORMATION

Part Number	CBS4LEDS-LO-DIF-DD-DALI
MIC	AUB02211050002
Description	LP Premium Odyssey Quantum LED Diffused Batten with LED Emergency Pod with DALI Driver
Construction	Powder Coated Steel Body with Acrylic Prismatic Diffuser and PC/ABS End Caps
Mounting	Surface Mount
Dimensions L x W x H	1271mm x 120mm x 108mm
Operating Mode	Sustained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Driver / Ballast	LED Driver – LCA 50w 350-1050mA
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	2438lm @128lm/W
Power Consumption	19 Watts (Lamps ON), 0.4 Watts (Lamps OFF)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
8002695	PCA:LED Strip 8S6P, ALS-13-840-0-02-B
1330056	LED Driver – LCA 50w 350-1050mA
CLIFE-CKIT-NP	Lifelight, Control Only, LP, No Plug
8003060	PCA: New DALI #CT10629-Ax