



CWB4LEDS-P-DD-DALI

CLEVERTRONICS LP ARGONAUT LED WEATHERPROOF BATTEN



Gen 1



Gen 2

PRODUCT INFORMATION

Catalogue Number	CWB4LEDS-P-DD-DALI
Description	LP Premium 4ft Argonaut Weatherproof Batten with DALI Driver and LED Emergency POD
Construction	Polycarbonate Base, Polycarbonate Diffuser and Captive Stainless Steel Clips
Mounting	Surface Mount
Dimensions L x W x H	1220mm x 110mm x 108mm
Weight	3.3kg
Operating Mode	Sustained
Testing System	DALI compatible
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Driver	Tridonic LCA 50W 350-1050mA ONE4ALL
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	4125 lm @ 96lm/W
Power Consumption	44 Watts (Lamps ON), 0.4 Watts (Lamps OFF)
IP Rating	IP66 (Batten), IP65 (POD)
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D63 C ₉₀ =D50 (Gen 1) C ₀ =D80 C ₉₀ =D80 (Gen 2)
Impact Rating	IK08

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
8002690	PCA:LED Strip Argonaut Standard inc tray
1330056	LED Driver - LC 50w 350-1050mA, ONEFORALL
CLIFE-PRO-CKIT-L850-NP	LifelightPro, Control Only, Batten, LP, NP
8002200	PCA:DALI Node, #CT10410-A3

DALI EM

LP LITHIUM IRON PHOSPHATE

PREMIUM

PROVEN PROJECT PERFORMANCE