

CLEVERTRONICS LP ARGONAUT LED WEATHERPROOF BATTEN – LOW POWER OUTPUT



PRODUCT INFORMATION

Part Number	CWB4LEDS-P-LO-DD-ZW
Description	LP Premium 4ft Argonaut weatherproof batten with LED Emergency POD with DALI driver
Construction	Polycarbonate base, polycarbonate diffuser and captive stainless steel clips with tamperproof screws
Mounting	Surface mount
Dimensions L x W x H	1220mm x 110mm x 108mm
Weight	3.3kg
Operating Mode	Sustained
Testing System	Zoneworks Computerised Testing
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Polycarbonate
Driver / Ballast	Tridonic LC 50W 350-1050mA ONE4ALL
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	3200 lm @ 100lm/W
Power Consumption	32 Watts (Lamps ON), 0.4 Watts (Lamps OFF)
IP Rating	IP66 (Batten), IP65 (POD)
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D80 C ₉₀ =D80
Impact Rating	IK08

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
8002692	PCA:LED Argonaut Stand&tray,1.2m,LMF36
1330056	LED Driver - LC 50w 350-1050mA,ONEFORALL
CLIFE-PRO-CKIT-L850-NP	LifelightPro,Control Only,Batten,LP, NP
8001450	PCA:Powerline Node ZW, #CT10310-A6

