

CLEVERTRONICS LP ARGONAUT LED WEATHERPROOF BATTEN – LOW POWER OUTPUT WITH MICROWAVE MOTION SENSOR (ZONWORKS XT HIVE)



PRODUCT INFORMATION

Catalogue Number	CWB4LEDS-P-LO-MS-HL-HV
MIC	AUB02820090001
Description	LP Premium 4ft Argonaut weatherproof batten with LED Emergency POD and Hi/Lo Microwave Sensor Control of the Lamps (10%-100%)
Construction	Polycarbonate base, polycarbonate diffuser and captive stainless steel clips with tamperproof screws
Mounting	Surface Mount
Dimensions L x W x H	1225mm x 157mm (POD) x 111mm, (Batten width 110mm)
Weight	3.3kg
Operating Mode	Sustained Minimum to maximum light control via the microwave sensor. Low level comfort light when no presence detected ramping to maximum when presence detected
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Driver / Ballast	LED MSHL Driver - 65w 600-1200mA, 35-55V
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	3217lm
Power Consumption	33 Watts (Lamps ON), 1 Watts (Lamps OFF)
IP Rating	IP66 (Batten), IP65 (POD)
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D80 C ₉₀ =D80
Impact Rating	IK08

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
8002692	PCA:LED Argonaut Stand&tray, 1.2m,LMF36
1330090	LED MSHL Driver - 65w 600-1200mA, 35-55V
AUM02870030001	CLIFE-PRO-CKIT-HV-L850-NP
8003190	PCA: RF Node CT10678-Ax internal antenna

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order