




CLEVERTRONICS L10 ARGONAUT LED WEATHERPROOF BATTEN



Gen 1



Gen 2

PRODUCT INFORMATION

Catalogue Number	LWB4LEDS-P-DALI
Description	L10 Optimum Argonaut Weatherproof Batten with LED Emergency POD
Construction	Polycarbonate Base, Polycarbonate Diffuser and Captive Stainless Steel Clips
Mounting	Surface Mount
Dimensions L x W x H	1220mm x 110mm x 108mm
Weight	3.3kg
Operating Mode	Sustained
Testing System	DALI compatible
Battery	Lithium Nanophosphate, 3.2V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Driver	OSRAM OT FIT, 50,000hr
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	4125 lm @ 96lm/W
Power Consumption	44 Watts (Maintained Standby), 0.4 Watts (Standby)
IP Rating	IP66 (Batten), IP65 (POD)
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D63 C ₉₀ =D50 (Gen 1) C ₀ =D80 C ₉₀ =D80 (Gen 2)
Impact Rating	IK08

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead,noBRKT
8002690	PCA:LED Strip Argonaut Standard inc tray
1330030	LED Driver - Argonaut Standard
LLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,L10, NP
8002200	PCA:DALI Node, #CT10410-A3

DALI EM

