

CLEVERTRONICS L10 ARGONAUT LED WEATHERPROOF BATTEN



PRODUCT INFORMATION

| | |
|-----------------------|--|
| Catalogue Number | LWB4LEDS-P-HV |
| MIC | AUB01820010001 |
| Description | L10 Optimum 4ft Argonaut Weatherproof Batten with LED Emergency POD |
| Construction | Polycarbonate Base, Polycarbonate Diffuser and Captive Stainless Steel Clips with Tamperproof Screws |
| Mounting | Surface Mount |
| Dimensions L x W x H | 1225mm x 157mm x 111mm |
| Weight | 3.3kg |
| Operating Mode | Sustained |
| Testing System | Zoneworks XT HIVE (RF) |
| Battery | Lithium Nanophosphate, 3.3V 2500mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Diffuser | Polycarbonate |
| Driver / Ballast | Driver: 57w, 800-1050mA |
| Lamp(s) | LED strip module, 4,000K natural white, 149,000h life [L70/B50 Ta 40°C], Ra>80 |
| Operating Voltage | 240V AC; 50Hz |
| Power Factor | 0.95 |
| Total lumen output | 4300 lm @ 105lm/W |
| Power Consumption | 41 Watts (Lamps ON), 0.4 Watts (Lamps OFF) |
| IP Rating | IP66 (Batten), IP65 (POD) |
| Operating Temperature | 0°C to 40°C |
| AS2293 Classification | C ₀ =D80 C ₉₀ =D80 |
| Impact Rating | IK08 |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------------|---|
| 1530050 | Battery, L10 3.3V 2500mAh 70mm lead, no Bracket |
| 8002690 | PCA:LED Strip Argonaut Stand & tray,1.2mm |
| LLIFE-PRO-CKIT-NP | LifelightPro,Control Only,Batten,L10, NP |
| 8003190 | PCA: RF Node CT10678-Ax internal antenna |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order