

CLEVERTRONICS L10 ARGONAUT LED WEATHERPROOF BATTEN LOW POWER OUTPUT (ZONENWORKS XT HIVE)



PRODUCT INFORMATION

Catalogue Number	LWB4LEDS-P-LO-DD-HV
MIC	AUB01820140001
Description	L10 Optimum 4ft Argonaut Weatherproof Batten Low Power Output with Dali Driver and LED Emergency POD
Construction	Polycarbonate Base, Polycarbonate Diffuser and Captive Stainless Steel Clips with Tamperproof Screws
Mounting	Surface Mount
Dimensions L x W x H	1225mm x 157mm x 111mm
Weight	3.3kg
Operating Mode	Sustained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Driver / Ballast	LED Driver - LCA 50w 350-1050mA, ONEFORALL
Lamp(s)	LED strip module, 4,000K natural white, 149,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	3200lm @ 100lm/W
Power Consumption	32 Watts (Lamps ON), 0.4 Watts (Lamps OFF), 35W (MAX during 16hrs charge)
IP Rating	IP66 (Batten), IP65 (POD)
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D80 C ₉₀ =D80
Impact Rating	IK08

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead,no Brkt (Qty 2)
8002910	PCA:LL-Pro L10 550mA .#CT10142-L8 CTP
1330056	LED Driver - LCA 50w 350-1050mA, ONEFORALL
LLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,L10, NP
8003190	PCA: RF Node CT10678-Ax internal antenna

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order