

## CLEVERTRONICS L10 ARGONAUT LED WEATHERPROOF BATTEN LOW POWER OUTPUT, DALI DRIVER



### PRODUCT INFORMATION

Catalogue Number	LWB4LEDS-P-LO-DD
MIC	AUB01320140001
Description	L10 Optimum 4ft Argonaut Weatherproof Batten Low Power Output with Dali Driver and LED Emergency POD, Enabled with Clevertest Plus
Construction	Polycarbonate Base, Polycarbonate Diffuser and Captive Stainless Steel Clips with Tamperproof Screws
Mounting	Surface Mount
Dimensions L x W x H	1225mm x 110mm (Batten) x 111mm, (POD width 157mm)
Weight	3.3kg
Operating Mode	Sustained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Driver / Ballast	LED Driver - LCA 50w 350-1050mA, ONEFORALL
Lamp(s)	LED strip module, 4,000K natural white, 149,000h life [L70/B50 Ta 40°C], 89,000h life [L80/B10 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	3200lm @ 100lm/W (based on non-emergency version)
Power Consumption	35W (MAX Charge - Lamp ON), 32W (Standby Lamp ON), 0.4W (Standby Lamp OFF)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C <sub>0</sub> =D80 C <sub>90</sub> =D80
Impact Rating	IK08

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead,no Brkt (Qty 2)
8002910	PCA:LL-Pro L10 550mA .#CT10142-L8 CTP
1330056	LED Driver - LCA 50w 350-1050mA, ONEFORALL
LLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,L10, NP

*The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order*