

CLEVERTRONICS L10 ARGONAUT LED WEATHERPROOF BATTEN – LOW POWER OUTPUT



PRODUCT INFORMATION

Part Number	LWB4LEDS-P-LO-ZW
Description	L10 Lithium Nanophosphate 4ft Argonaut weatherproof batten with LED Emergency POD
Construction	Polycarbonate base, polycarbonate diffuser and captive stainless steel clips with tamperproof screws
Mounting	Surface mount
Dimensions L x W x H	1220mm x 110mm x 108mm
Weight	3.3kg
Operating Mode	Sustained
Testing System	Zoneworks Computerised Testing
Battery	Lithium Nanophosphate, 3.2V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Polycarbonate
Driver / Ballast	OSRAM OT FIT, 50,000hr
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	3200 lm @ 100lm/W
Power Consumption	32 Watts (Lamps ON), 0.4 Watts (Lamps OFF)
IP Rating	IP66 (Batten), IP65 (POD)
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D80 C ₉₀ =D80
Impact Rating	IK08

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead,noBRKT
8002692	PCA:LED Argonaut Stand&tray,1.2m,LMF36
1330035	LED Driver - Argonaut Low Output
LLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,L10, NP
8001450	PCA:Powerline Node ZW, #CT10310-A6

