

CLEVERTRONICS L10 ARGONAUT LED WEATHERPROOF BATTEN & MICROWAVE SENSOR



PRODUCT INFORMATION

Catalogue Number	LWB4LEDS-P-MS-HL-HV
MIC	AUB01820020001
Description	L10 Optimum 4ft Argonaut Weatherproof Batten with LED Emergency POD and Hi/Lo Microwave Sensor Control of the Lamps (10%-100%)
Construction	Polycarbonate Base, Polycarbonate Diffuser and Captive Stainless Steel Clips with Tamperproof Screws
Mounting	Surface Mount
Dimensions L x W x H	1225mm x 157mm x 111mm
Weight	3.3kg
Operating Mode	Sustained Minimum to maximum light control via the microwave sensor. Low level comfort light when no presence detected ramping to maximum when presence detected
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Driver / Ballast	Driver: 65w 600-1200mA, 35-55V
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	4000 lm @ 97lm/W
Power Consumption	41 Watts (Lamps ON), 0.4 Watts (Lamps OFF)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D80 C ₉₀ =D80
Impact Rating	IK08

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	Battery, L10 3.3V 2500mAh 70mm lead, no Bracket
8002690	PCA:LED Strip Argonaut Stand & tray,1.2m
1330090	LED MSHL Driver - 65w 600-1200mA, 35-55V
LLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,L10, NP
8003190	PCA: RF Node CT10678-Ax internal antenna

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order