

## CLEVERTRONICS L10 ARGONAUT LED WEATHERPROOF BATTEN



### PRODUCT INFORMATION

Part Number	LWB4LEDS-P-ZW
Description	L10 Lithium Nanophosphate Argonaut weatherproof batten with LED Emergency POD
Construction	Polycarbonate base, polycarbonate diffuser and captive stainless steel clips with tamperproof screws
Mounting	Surface mount
Dimensions L x W x H	1220mm x 110mm x 108mm
Weight	3.3kg
Operating Mode	Sustained
Testing System	Zoneworks Computerised Testing
Battery	Lithium Nanophosphate, 3.2V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Polycarbonate
Driver / Ballast	Tridonic LC 57W 800-1050mA
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	4300 lm @ 105lm/W
Power Consumption	44 Watts (Lamps ON), 0.4 Watts (Lamps OFF)
IP Rating	IP66 (Batten), IP65 (POD)
Operating Temperature	0°C to 40°C
AS2293 Classification	C <sub>0</sub> =D80 C <sub>90</sub> =D80
Impact Rating	IK08

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead,noBRKT
8002690	PCA:LED Strip Argonaut Standard inc tray
1330057	LED Driver - LC 57w 800-1050mA,flexC Ip
LLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,L10, NP
8001450	PCA:Powerline Node ZW, #CT10310-A6

