




## ARGO-600-SEN-LP

CLEVERTRONICS LP ARGO LED WEATHERPROOF BATTEN  
WITH INTEGRAL BATTERY, MICROWAVE SENSOR AND SWITCHABLE COLOUR



### PRODUCT INFORMATION

Part Number	ARGO-600-SEN-LP
MIC	AUB02320460001
Description	LP Premium ARGO 600mm LED Weatherproof Emergency Batten with Integral Battery, Microwave Sensor (Hi/Lo) and Switchable Colour, Enabled with Clevertest Plus
Construction	Polycarbonate Base and Diffuser with Captive Stainless-Steel Clips (SS301)
Mounting	Surface mount
Dimensions L x W x H	655mm x 121mm x 88mm
Weight	1.5 kg
Operating Mode	Sustained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Polycarbonate
Driver / Ballast	LED Driver – 20w Stallion, MS-HL
Lamp(s)	Dual LED strip module, 3,000K warm white, 5,700K cool white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Total lumen output	2150lm (120lm/W @4000K, based on non-emergency), details see table Page 2
Power Consumption	see table Page 2
IP Rating	IP65
Operating Temperature	0°C to 40°C
Impact Rating	IK08
AS2293 Classification	C <sub>0</sub> =D40 C <sub>90</sub> =D25
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	



## ARGO-600-SEN-LP

CLEVERTRONICS LP ARGO LED WEATHERPROOF BATTEN  
WITH INTEGRAL BATTERY, MICROWAVE SENSOR AND SWITCHABLE COLOUR



### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	BATT:LP 3.2V 3200mAh 70mm lead,no BRKT.
AUM02370080001 CLIFE-PRO-CKIT-NP-335	Lifelight Pro, Control Only, Batten, LP, OWC
1330087-A	LED Driver - 20w Stallion, MS-HL, S-MNT
8002848	PCA: LED Strip for 2ft Argonaut Tri-Colour (x2)
8002700	PCA:LED Strip 2S4P, Eco Argonaut (EM)

Colour	Power Consumption				Total Lumen Output
	MAX Charge Lamp ON	Standby Lamp ON	Standby Lamp MIN (10%)	Standby Lamp OFF	
3000K	22 W	19 W	2 W	0.4 W	1950 lm
4000K	21 W	18 W	2 W	0.4 W	2150 lm
5700K	22 W	19 W	2 W	0.4 W	2040 lm

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order