

CLEVERTRONICS LP ODYSSEY QUANTUM WIRE GUARD BATTEN



PRODUCT INFORMATION

Part Number	CBS2L4S-LT-WG-DALI
MIC	AUB02210930002
Description	LP Premium 2 x LED tube 4ft Odyssey Quantum wire guard batten with LED Emergency pod
Construction	Powder coated steel body with PC/ABS end caps
Mounting	Surface mount
Dimensions L x W x H	1274mm x 120mm x 110mm
Weight	3.9kg
Operating Mode	Sustained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 3.2V 3000mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Wire Guard
Lamp(s)	2x Philips CorePRO LEDtube T8, Col. 840, 30,000hours
Operating Voltage	240V AC; 50Hz
Total lumen output	3800 lm @ 93lm/W (based on the non-emergency version)
Power Consumption	41 Watts (Standby), 1.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560150	BATT:LiFePO4 3.2V 3.0Ah 70mm lead,noBRKT
3170080	LED TUBE 20W/840, 1.2m
CLIFE-CKIT-NP	Lifelight, Control Only, LP, No Plug
8003060	PCA: DALI Node #CT10629-Ax

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

