

CLEVERTRONICS L10 1200MM (4FT) NON-MAINTAINED BATTEN REPLACEMENT (Zoneworks)



PRODUCT INFORMATION

Catalogue Number	LBS4N-ZW
Description	L10 Optimum 1200mm (4ft) non-maintained bare batten replacement utilising the Lifelight - High Performance, Emergency Light with Premium Lithium Battery Technology
Construction	Powder coated steel body and ABS/polycarbonate end caps
Mounting	Surface mount
Dimensions L x W x H	1220mm x 110mm x 50mm
Operating Mode	Non-maintained
Testing System	Zoneworks computerised testing
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x 3W LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 Watts
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D63 C ₉₀ =D63

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt.
1100830	Lifelight Pro Head Assembly, Round
LLIFE-PRO-CKIT	Lifelight Pro, Control Only, LP/L10
8001450	PCA:Powerline Node ZW, #CT10310-A6

ZONEWORKS

L10™ OPTIMUM
LITHIUM BATTERY RANGE

Version: June 2016-I

www.clevertronics.com.au