

## CLEVERTRONICS 24V TEMPORARY CLEVERFIT EXIT



### PRODUCT INFORMATION

Part Number	TCFLED24V
Description	Temporary 24V Cleverfit Exit with flex and plug - for temporary lighting applications on construction sites
Construction	ABS Body and Diffuser with Polycarbonate clear decal cover and 1m flex and plug for temporary lighting applications on construction sites
Mounting	Chain Suspension or Wall mount
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.2kg
Operating Mode	Maintained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 3000mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	4 x LED lamp bar assembly 50,000 hours
Operating Voltage	19-28V DC
Power Consumption	1.5 Watts
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D4 C <sub>90</sub> =E2.5
Viewing Distance	24m

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560150	BATT:LiFePO4 3.2V 3.0Ah 70mm lead,noBRKT

*The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order*

**TEMP** LITHIUM IRON  
PHOSPHATE  
TEMPORARY