

CLEVERTRONICS 24V TEMPORARY WEATHERPROOF EXIT



PRODUCT INFORMATION

Part Number	TWELED24V
Description	Temporary 24V weatherproof Emergency Exit with 1m flex and plug for temporary lighting applications on construction sites (flex and plug supplied loose – cable entry and termination to be carried out by the installer)
Construction	Polycarbonate clear cover, Glass reinforced nylon PA66 base
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	410mm x 272mm x 100mm
Weight	2.8kg
Operating Mode	Maintained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 3000mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	4 x LED lamp bar assembly 50,000 hours
Operating Voltage	19-28V DC
Power Consumption	1.5 Watts
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D2.5 C ₉₀ =E1.6
Impact Rating	IK10
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560150	BATT:LiFePO4 3.2V 3.0Ah 70mm lead,noBRKT

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

TEMP LITHIUM IRON
PHOSPHATE
TEMPORARY