



CLEVERTRONICS LP JUMBO WALL MOUNTED WEATHERPROOF EXIT



PRODUCT INFORMATION

Catalogue Number	CJWELED-32-DALI-WM-R
Description	LP Premium Wall Mounted IP66/67 LED Jumbo Weatherproof Exit
Construction	Base Material: Polycarbonate Diffuser Cover Material: Polycarbonate
Mounting	Wall Mount
Dimensions L x W x H	130mm x 380mm x 280mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	DALI compatible
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Running Man (Arrow combinations not available in 32m viewing distance)
Lamp(s)	Twin 6 x High Intensity, Low Energy LED, Surface Mounted onto a Replaceable Lamp Bar - 100,000hour
Operating Voltage	240V AC; 50Hz
Power Consumption	3.7 Watts (Standby), 4.9 Watts (Max)
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =A1.25 C ₉₀ =E1.25
Impact Rating	IK08 (side surface) IK09 (front surface)
Viewing Distance	32m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	BATT:LP 3.2V 3200mAh 200mm lead,BRKT.
8002120	PCA:DLED Cleverfit LightStrip,CT10152-D2
CJWELED-32-CKIT	WP LED Exit, Control Kit, LP
8002200	PCA:DALI Node, #CT10410-A3

DALI EM

LP LITHIUM IRON PHOSPHATE
PREMIUM
 PROVEN PROJECT PERFORMANCE