

## CLEVERTRONICS LP JUMBO WEATHERPROOF EXIT



### PRODUCT INFORMATION

Part Number	CJWELED-40-DALI-WM-R
MIC	AUA02220030102
Description	LP Premium wall mount IP66/67 Jumbo weatherproof Exit
Construction	Base material: Polycarbonate Diffuser cover material: Polycarbonate
Mounting	Wall mount
Dimensions L x W x H	560mm x 280mm x 130mm
Weight	5.5kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Running man (Must specify diffuser combination)
Lamp(s)	4 x (5 x high intensity, low energy LED), surface mounted onto a replaceable lamp bar - 100,000hour
Operating Voltage	240V AC; 50Hz
Power Consumption	3.0 Watts (Standby), 5.0 Watts (Max)
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
AS2293 Classification	C <sub>0</sub> =E1.6 C <sub>90</sub> =E1.25
Impact Rating	IK08 (side surface) IK09 (front surface)
Viewing Distance	40m

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	BATT:LP 3.2V 3200mAh 200mm lead,BRKT.
8002122	PCA:Duris E5 LED Strip 5LED ,CT10152-D3
CJWELED-40-CKIT	WP LED Exit, Control Kit, LP
8003060	PCA: DALI Node #CT10629-Ax

