

## CLEVERTRONICS LP JUMBO WEATHERPROOF EXIT



### PRODUCT INFORMATION

Part Number	CJWELED-40-HV-WM-R
MIC	AUA02820030001
Description	LP Premium Jumbo Weatherproof Exit, Wall mounted
Construction	Base material: Polycarbonate Diffuser cover material: Polycarbonate
Mounting	Wall mount
Dimensions L x W x H	560mm x 280mm x 130mm
Weight	5.5kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Running man (Must specify diffuser combination)
Lamp(s)	4 x (5 x high intensity, low energy LED), surface mounted onto a replaceable lamp bar - 100,000hour
Operating Voltage	240V AC; 50Hz
Power Consumption	3.0 Watts (Standby), 5.0 Watts (Max)
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
AS2293 Classification	C <sub>0</sub> =E1.6 C <sub>90</sub> =E1.25
Impact Rating	IK08 (side surface) IK09 (front surface)
Viewing Distance	40m

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	BATT:LP 3.2V 3200mAh 200mm lead,BRKT.
8002122	PCA:LL-Pro L10 Driver 550mA .#CT10142-L5
CJWELED-40-CKIT	WP LED Exit, Control Kit, LP
8003190	PCA: RF Node CT10678-A9 Int Antenna

*The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order*