



CJWELED-40-WM-R

CLEVERTRONICS LP JUMBO WEATHERPROOF WALL MOUNT EXIT



PRODUCT INFORMATION	
Part Number	CJWELED-40-WM-R
MIC	AUA02320030001
Description	LP Premium IP66/67 Weatherproof Wall Mount Jumbo Exit, Enabled with Clevertest Plus
Construction	Base material: Polycarbonate Diffuser cover material: Polycarbonate
Mounting	Wall mount
Dimensions L x W x H	560mm x 130mm x 280mm
Weight	5.5kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Running man (Must specify diffuser combination)
Lamp(s)	4 x (5 x high intensity LED), surface mounted onto a replaceable lamp bar – 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 5.3 Watts (Max)
IP Rating	IP66/IP67
IK Rating	IK08 (side surface) IK09 (front surface)
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=E1.6 C90=E1.25
Viewing Distance	40m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550010	BATT:LP 3.2V 3200mAh 200mm lead,BRKT.
8002122	PCA:Duris E5 LED Strip 5LED ,CT10152-D4 (Qty 4)
AUM02370120001 CJWELED-40-CKIT	WP LED Exit, Control Kit, LP, OWC

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order