

CLEVERTRONICS LP WEATHERPROOF EXIT



PRODUCT INFORMATION

| | |
|-----------------------|---|
| Catalogue Number | CWELED-HV |
| MIC | AUA02820010001 |
| Description | LP Premium weatherproof Emergency EXIT |
| Construction | Polycarbonate clear cover, glass reinforced nylon PA66 base |
| Mounting | Wall, ceiling single-sided & ceiling double-sided |
| Dimensions L x W x H | 410mm x 100mm x 272mm |
| Weight | 2.8kg |
| Operating Mode | Maintained |
| Testing System | Zoneworks XT HIVE (RF) |
| Battery | Lithium Iron Phosphate, 3.2V 1500mAh |
| Charging Method | Intelligent current limited constant voltage |
| Diffuser | All directional inserts included in the box |
| Lamp(s) | 6 x LED lamp bar assembly 100,000 hours |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 2.7 Watts (Standby), 5.1 Watts (Max) |
| IP Rating | IP66/IP67 |
| Operating Temperature | 0°C to 40°C |
| AS2293 Classification | C ₀ =E2 C ₉₀ =E2 |
| Impact Rating | IK10 |
| Viewing Distance | 24m |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|--|
| 1550190 | BATT:LP 3.2V 1500mAh 390mm lead, noBRKT. |
| 8002120 | PCA:DLED Cleverfit LightStrip,CT10152-D2 |
| 8003190 | PCA: RF Node CT10678-Ax internal antenna |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order