

CLEVERTRONICS L10 JUMBO WEATHERPROOF WALL MOUNT EXIT (ZONWORKS XT HIVE)



PRODUCT INFORMATION

Catalogue Number	LJWELED-32-HV-WM-R
MIC	AUA01820100001
Description	L10 Premium Wall Mounted IP66/67 Weatherproof Exit
Construction	Base material: Polycarbonate Diffuser cover material: Polycarbonate
Mounting	Wall mount, Single-sided
Dimensions L x W x H	130mm x 380mm x 280mm
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, , 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Running man (Must specify diffuser combination)
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	4W (standby) 5.5W (max during 16-hour charge)
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =A1.25 C ₉₀ =E1.25
Impact Rating	IK08 (side surface) IK09 (front surface)
Viewing Distance	32m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	BATT:LP 3.3V 2500mAh 200mm lead,BRKT.
8002120	PCA:DLED Cleverfit LightStrip,CT10152-D2 (Qty 2)
AUM01870220001 LJWELED-32-CKIT-HV	WP LED Exit, Control Kit, HV, L10 (incl. Hive node)
8003190	PCA: RF Node CT10678-A9 Int Antenna

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order