

CLEVERTRONICS L10 OPTIMUM JUMBO WEATHERPROOF WALL MOUNT LED EXIT (ZONWORKS)



PRODUCT INFORMATION

Catalogue Number	LJWELED-32-ZW-WM-R
Description	LED L10 OPTIMUM Wall Mount IP66/67 Jumbo Weatherproof Exit, 32 metre viewing Distance
Construction	Base Material: Polycarbonate Diffuser Cover Material: Polycarbonate
Mounting	Wall Mount, Single Sided
Dimensions D x W x H	130mm x 380mm x 280mm
Operating Mode	Maintained
Testing System	Zoneworks Computerised Testing
Charging Method	Intelligent current limited constant voltage charger
Diffuser	(must specify diffuser combination)
Lamp(s)	Twin 6 x high intensity, low energy LED, surface mounted onto a replaceable lamp bar - 100,000hour
Operating Voltage	240V
Power Consumption	3.7W (standby) 4.9W (max during 16 hour charge)
IP Rating	IP66/67
Impact Rating	IK08 (side surface) IK09 (front surface)
Operating Temperature	1° to 40°C
AS/NZ2293 Classification	C ₀ =A1.25 C ₉₀ =E1.25

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	Battery: L10 3.3V, 2.5AH, Li-ion
8002336	PCA: L/CJWELED-32 Driver, #CT10164-L4
8002120	PCA: DLED Cleverfit LightStrip, CT10152-D2
8001450	PCA: Zoneworks Powerline Node, #CT10310-A6

