

## CLEVERTRONICS L10 JUMBO WEATHERPROOF EXIT



### PRODUCT INFORMATION

Part Number	LJWELED-40-DALI-WM-R
MIC	AUA01220040102
Description	L10 Lithium Nanophosphate wall mount IP66/67 Jumbo weatherproof Exit
Construction	Base material: Polycarbonate Diffuser cover material: Polycarbonate
Mounting	Wall mount
Dimensions L x W x H	560mm x 280mm x 130mm
Weight	5.5kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Running man (Must specify diffuser combination)
Lamp(s)	4 x (5 x high intensity, low energy LED), surface mounted onto a replaceable lamp bar - 100,000hour
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 5.3 Watts (Max)
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
AS2293 Classification	C <sub>0</sub> =E1.6 C <sub>90</sub> =E1.25
Impact Rating	IK08 (side surface) IK09 (front surface)
Viewing Distance	40m

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	BATTERY:L10 3.3V 2.5AH 200mm lead, BRKT.
8002122	PCA:Duris E5 LED Strip 5LED ,CT10152-D3
LJWELED-40-CKIT	WP LED Exit, Control Kit, L10
8003060	PCA: DALI Node #CT10629-Ax

