



LWELED-ZW-WM

CLEVERTRONICS L10 WEATHERPROOF WALL MOUNT EXIT



PRODUCT INFORMATION

Part Number	LWELED-ZW-WM
MIC	AUA01120120001
Description	L10 Optimum Wall Mounted IP66/67 Weatherproof Exit
Construction	Polycarbonate Clear Cover, Polycarbonate Base
Mounting	Wall mount, Single-sided
Dimensions L x W x H	380mm x 130mm x 190mm
Weight	2.7kg
Operating Mode	Maintained
Testing System	Zoneworks Computerised Testing
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x High Intensity LED, surface mounted onto a replaceable Lamp Bar - 100,000hrs
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 3.8 Watts (Max)
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =E1.6 C ₉₀ =C1.6
Impact Rating	IK08 (side surface) IK09 (front surface)
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	BATTERY:L10 3.3V 2.5AH 200mm lead, Brkt
AUM01170190001 LWELED-CKIT-ZW-50	WP LED Exit, Control Kit, L10, OWC, 50mA, ZW (incl ZW node)
8002120	PCA:DLED Cleverfit LightStrip,CT10152-D2
8001450	PCA:Powerline Node ZW, #CT10310-A6

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order